



SPECIFICATION SHEET

Item Code: **JN-LED/G2**
Description: **JUNGLE G2 LED 240 Watt**

	⚡ 100-277V
PPF	624 μmol/s
LED Efficacy	up to 2.6 μmol/j
Input Power	240W
Input Voltage	100-277V (Optional 208-480V)
Frequency	50/60 Hz
Dimming	0-10V
Light Distribution	120°
Power Factor	>0.9
Rated Lifetime	>50,000 Hours
Fixture L x W x H	46.26" x 20.47" x 2.76" (1175 x 520 x 70mm)
Max Ambient Temperature	104°F / 40°C
Weight (Incl. Driver)	13.45lbs / 6.10kg
Certification Standard	ETL, UL8800, UL1598 Wet Location, IP65 & CE

Max Amperage by Voltage Service

Voltage	120V	208V	240V	277V
Amperage	2.0A	1.15A	1.0A	0.87A

Plug Type

- NEMA 6-15P AC Power Cord
- NEMA 5-15P AC Power Cord*
- Power Cord Adapter (240V/120V)
- Power Cord with Lead Wire (Pigtail)*

* Optional hardware/accessory

Accessories

- 5' RJ12 to RJ12 Link Cable
- RJ12 T-Splitter
- V Hanger (2)
- 1.5 feet Push-lock Daisy Chain Cable
 - 120V: up to 3 fixtures (daisy chain)
 - 240V: up to 6 fixtures (daisy chain)
 - 277V: up to 7 fixtures (daisy chain)

Extension Cord

- 10 feet AC Power Cord
- 15 feet AC Power Cord*

Product Highlights

- Full-cycle Spectrum LED
- External Control Connectivity
- Energy Efficient (40% less energy than HPS lamps)
- Corrosion Resistance
- Daisy Chain Capability
- IP 65, UL 1598 Wet Location
- Surge Protection
- Warranty: 3-Year Standard, 5-Year Limited

